DECLARATION OF PERFORMANCE

DoP number: 12453530-B3W1245

Product name:

AMBERLEY RED MULTY ECO BRICK

Identification code of product-type is DoP-number



Wienerberger NV
Kapel ter Bede 121 - 8500 Kortrijk
Belgium

unprotected masonry System 2+ EN 771-1:2011+A1:2015

0749

Intended use in masonry walls, colums and partitions for:

Assessment and verification of constancy of performance:

Harmonised standard:

Notified body/ies:

Dimensions and tolerances			T1	R1	
Length:	mm	215	± 6	9	^
Width:	mm	65	± 3	5	
Height:	mm	65	± 3	5	
Tolerance:	category		T1	•	
Range:	category	R1			
Flatness of bed faces:	mm	NPD			
Plane parallelism:	mm	NPD			
Configuration					
Group of the unit:	-	1			
Volume of all formed voids:	%	NPD			
Volume of frogs:	%	NPD			actual configuration may vary slightly
Density					
Gross dry density:	kg/m³	1650			
Net dry density:	kg/m³	1700			
Tolerance:	category / %	D1 / 10			
Compressive strength for Category I pro	duct				
Perpendicular to bedface:	N/mm²	25			
Perpendicular to header:	N/mm²	NPD			
Perpendicular to header 2:	N/mm²		NPD		
Bond strength:	N/mm²		NPD		
Thermal conductivity λ10,dry,unit:	W/(m·K)	0,690			Determination method EN 1745:2012: S1
Water vapour permeability:	-	μ = 5/10)	Tabulated min. and max. value according EN 174
Durability:	category	F2			According EN 772-22
Water absorption:	%	14			According EN 772-21
Initial rate of water absorption:	kg/(m²·min)	3-8			According EN 772-11
Active soluble salt content:	category	S2			According EN 772-5
Moisture movement:	mm/m		NPD		
Reaction to fire:	class		A 1		EN 13501-1
Dangerous substances:	-	NPD			

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Wienerberger NV Kapel ter Bede 121 - 8500 Kortrijk Belgium