

DECLARATION OF PERFORMANCE

DoP number: 12760111-B1W1275

Product name:

ELIGNIA SILVA GREIGE

Identification code of product-type is DoP-number



Wienerberger NV

Kapel ter Bede 121 - 8500 Kortrijk

Belgium

Intended use in masonry walls, columns and partitions for:

Assessment and verification of constancy of performance:

Harmonised standard:

Notified body/ies:

unprotected masonry


System 2+

EN 771-1:2011+A1:2015

0749

Declared performance/s of a U - masonry unit

Dimensions and tolerances			T2	R2
Length:	mm	288	± 4	5
Width:	mm	90	± 2	3
Height:	mm	48	± 2	2
Tolerance:	category	T2		
Range:	category	R2		
Flatness of bed faces:	mm	NPD		
Plane parallelism:	mm	NPD		
Configuration				
Group of the unit:	-	1		
Volume of all formed voids:	%	NPD		
Volume of frogs:	%	NPD		
Density				
Gross dry density:	kg/m ³	1450		
Net dry density:	kg/m ³	1850		
Tolerance:	category / %	D1 / 10		
Compressive strength for Category I product				
Perpendicular to bedface:	N/mm ²	15		
Perpendicular to header:	N/mm ²	NPD		
Perpendicular to header 2:	N/mm ²	NPD		
Bond strength:	N/mm ²	NPD		
Thermal conductivity λ_{10} ,dry,unit:	W/(m·K)	0,690		
Water vapour permeability:	-	$\mu = 5/10$		
Durability:	category	F2		
Water absorption:	%	17		
Initial rate of water absorption:	kg/(m ² ·min)	1-5		
Active soluble salt content:	category	S2		
Moisture movement:	mm/m	NPD		
Reaction to fire:	class	A1		
Dangerous substances:	-	NPD		



actual configuration may vary slightly

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

2025-02-28 CEO Caroline Van De Velde

Wienerberger NV
Kapel ter Bede 121 - 8500 Kortrijk
Belgium