

# DECLARATION OF PERFORMANCE

DoP number: 34472040R003W1344

Product name:

KIR 17/8 2DF KK1 B-Lochung

Identification code of product-type is DoP-number




Wienerberger GmbH  
Oldenburger Allee 26 - 30659 Hannover  
Germany

Intended use in masonry walls, columns and partitions for:  
Assessment and verification of constancy of performance:  
Harmonised standard:  
Notified body/ies:

unprotected masonry  
System 2+  
EN 771-1:2011+A1:2015  
2510

## Declared performance/s of a U - masonry unit

Dimensions and tolerances			T2	R2
Length:	mm	240	± 4	5
Width:	mm	115	± 3	3
Height:	mm	113	± 3	3
Tolerance:	category	T2		
Range:	category	R2		
Flatness of bed faces:	mm	NPD		
Plane parallelism:	mm	NPD		
Configuration				
Group of the unit:	-	2		
Volume of all formed voids:	%	35		
Volume of frogs:	%	NPD		
Density				
Gross dry density:	kg/m <sup>3</sup>	1500		
Net dry density:	kg/m <sup>3</sup>	NPD		
Tolerance:	category / %	D2 / 5		
Compressive strength for Category I product				
Perpendicular to bedface:	N/mm <sup>2</sup>	≥35		
Perpendicular to header:	N/mm <sup>2</sup>	NPD		
Perpendicular to header 2:	N/mm <sup>2</sup>	NPD		
Bond strength:	N/mm <sup>2</sup>	NPD		
Thermal conductivity λ <sub>10,dry,unit</sub> :	W/(m·K)	0		
Water vapour permeability:	-	μ = 50/100		
Durability:	category	F2		
Water absorption:	%	6		
Initial rate of water absorption:	kg/(m <sup>2</sup> ·min)	0-1.5		
Active soluble salt content:	category	S2		
Moisture movement:	mm/m	NPD		
Reaction to fire:	class	A1		
Dangerous substances:	-	NPD		



actual configuration may vary slightly

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

2019-06-05 CEO Jürgen Habenbacher

Wienerberger GmbH  
Oldenburger Allee 26 - 30659 Hannover  
Germany