

DECLARATION OF PERFORMANCE

DoP number: 34482530R003W1344

Product name:

KIR 282/18 DF Liko gedämpft voll

Identification code of product-type is DoP-number




Wienerberger GmbH
Oldenburger Allee 26 - 30659 Hannover
Germany

Intended use in masonry walls, columns and partitions for:
Assessment and verification of constancy of performance:
Harmonised standard:
Notified body/ies:

unprotected masonry
System 2+
EN 771-1:2011+A1:2015
2510

Declared performance/s of a U - masonry unit

Dimensions and tolerances			Tm	Rm
Length:	mm	240	± 6	9
Width:	mm	115	± 4	6
Height:	mm	52	± 3	4
Tolerance:	category		Tm	
Range:	category		Rm	
Flatness of bed faces:	mm	NPD		
Plane parallelism:	mm	NPD		
Configuration				
Group of the unit:	-	1		
Volume of all formed voids:	%	0		
Volume of frogs:	%	NPD		
Density				
Gross dry density:	kg/m³	1900		
Net dry density:	kg/m³	NPD		
Tolerance:	category / %	D1 / 10		
Compressive strength for Category I product				
Perpendicular to bedface:	N/mm²	≥15		
Perpendicular to header:	N/mm²	NPD		
Perpendicular to header 2:	N/mm²	NPD		
Bond strength:	N/mm²	0,15		
Thermal conductivity λ10,dry,unit:	W/(m·K)	NPD		
Water vapour permeability:	-	μ = 5/10		
Durability:	category	F2		
Water absorption:	%	8		
Initial rate of water absorption:	kg/(m²·min)	NPD		
Active soluble salt content:	category	S2		
Moisture movement:	mm/m	NPD		
Reaction to fire:	class	A1		
Dangerous substances:	-	NPD		



actual configuration may vary slightly

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

2020-07-23 CEO Jürgen Habenbacher

Wienerberger GmbH
Oldenburger Allee 26 - 30659 Hannover
Germany